

COMMERCIAL ROLLER LATCHES



RL300 Dimensions:

Body: 1" Wide x 3-3/8" Long x 1-5/8" Deep
 Strike: 1-11/16" Wide x 2-3/16" Long x 5/32" Thick

RL300 FEATURES

Automatic actuation: closing door causes the roller to fall into the strike's depression, holding the door closed.

Projection of the roller is easily adjusted using adjusting screws on the face of the unit; maximum projection of the roller is 3/8", allowing for variance in the door clearance.

Nylon roller with forged brass construction
 Meets ANSI/BHMAA156.16, E19091



RL320 Dimensions:

Body: 1-1/8" Wide x 2-1/4" Long x 1-3/4" Deep
 Strike: 1-1/8" Wide x 2-3/4" Long x 1/16" Thick

RL320 FEATURES

Door is held closed when the roller is actuated.

Projection of the roller is easily adjusted by turning knurled knob on back of latch; maximum projection of roller is 1/2", allowing for variance in door clearance.

Fits heavy-duty cylindrical lock cutout.

Nylon roller with brass and Stainless Steel construction
 Meets ANSI/BHMA A156.16, E19101

CODE COMPLIANCE



ANSI A156.16 E19091
 C-UBC-California Amended Uniform Builders Code
 NFPA 80 - National Fire Protection Association - 1999
 NFPA 101 - National Fire Protection - Life Safety

Part Number	Standard Finish
RL300	26D Satin Chrome 10B Oil Rubbed Bronze
RL320	26D Satin Chrome 10B Oil Rubbed Bronze

For additional finish options not listed, contact Sales Department for MOQ and lead times