



PD9500 Series

Sliding Door Mortise Lock with Emergency Egress

- Single-action deadbolt release for emergency egress
- Patented anti-binding winged deadbolt provides smooth operation for safety and security
- Adjustable strike relieves door and frame alignment headaches
- ADA Compliant Trim

SPECIFICATIONS

Door Thickness	1-3/4" (45mm) Standard 1-3/8" (35mm) Thin Door Kit available for XGT only 2" to 2-1/4" (50mm to 57mm) Thick Door Kit available
Backset	2-3/4" (70mm) 2-1/2" (63.5mm)
Lever Spindle	8 x 8mm square
Thumbturn Spindle	5 x 5mm square
Center to Center Distance	Lever to cylinder: 3-7/8" (98mm) Lever to thumbturn: 2-11/16" (68mm)
Handing	Specify handing when ordering
Cylinder	Schlage C keyway 6 pin, 1-1/4" mortise cylinder with 2 keys (standard). SFIC and LFIC housing and cores available
CAM	CAM01-SCL Clover Cam
Material	Trim: Stainless Steel Lockcase: Heavy gauge Steel Deadbolt: Stainless Steel Faceplate/Strike: Stainless Steel Cylinder: Solid Brass

CODE COMPLIANCE



- ANSI/BHMA 156.36 Auxiliary Locks
- ANSI A117.1 Accessibility Code (ADA Compliant)


FINISH

- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- PVD4 Satin Brass (205, 221, 243, 244, 276, 318, 319, 320, 321, 346 and 509)
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze
- Please see Finish Solutions on INOX Website for special order finishes

APPLICATION


Available in multiple ANSI/BHMA functions, PD95 is suited for a wide range of applications including but not limited to: Hospitality, Healthcare, Commercial, and Offices.

FUNCTION




Privacy: 40

- Deadbolt can be retracted by inside lever or outside emergency coin release
- Thumbturn inside locks and unlocks deadbolt
- Outside lever is rigid at all times
- Inside lever can always retract deadbolt for emergency egress




Classroom: 70

- Deadbolt can be locked or unlocked by outside key
- No thumbturn on inside
- Outside lever is rigid at all times
- Inside lever can always retract deadbolt for emergency egress




Office / Entry: 50

- Deadbolt can be retracted or engaged by inside thumbturn or outside key
- Outside lever is rigid at all times
- Inside lever can always retract deadbolt for emergency egress



Security Communicating: 95

- Deadbolt can be retracted by outside key only
- Outside lever is rigid at all times
- No thumbturn on inside
- No lever on opposite side; blank or blind rosette only



Patio/Exit: 60


- Thumbturn inside locks or unlocks deadbolt
- Outside lever is rigid at all times
- No keyed cylinder outside; door cannot be opened from outside when locked
- Inside lever can always retract deadbolt for emergency egress

FUNCTION TABLE


	Code	Inside Lever	Outside Lever	Lockcase	Cylinder	Coin Turn	Thumbturn
Privacy	40	✓	✓	✓	✗	✓	✓
Inner Office	50	✓	✓	✓	✓	✗	✓
Patio/Exit	60	✓	✓	✓	✗	✗	✓
Classroom	70	✓	✓	✓	✓	✗	✗
Storeroom	80	✓	✓	✓	✓	✗	✗
Security Communicating	95	✓	✗	✓	✓	✗	✗

PD9500 SLIDING DOOR MORTISE LOCK WITH EMERGENCY EGRESS

COMPONENTS



LOCK DIMENSIONS




Description

- 1 PD9500 Series Lockcase
- 2 1" (25.4mm) heavy-duty brass bolt throw with self-retracting non-marring hooks
- 3 Adjustable strike for deadbolt; up to 1/4" vertical adjustability (6.35mm)
- 4 ADA Compliant thumbturn
- 5 Schlage C keyway, 6 pin 1-1/4" mortise cylinder
- 6 Heavy-duty stainless steel cast rose with choice of X Series lever design

HANDING

- Handing refers to the direction the door slides open. Example: If the door slides to the left to open, it is a left-handed door.
- Handing is determined from the exterior or key side of the door when facing into the room.



HOW TO ORDER A MORTISE LOCK FOR SLIDING DOOR

HOW TO ORDER STANDARD LOCKSETS


To order locksets with a non-standard specification, please describe the additional requirements in the same sequence as below. Please see price book for parts or additional service upcharge.

Rose	Lever	Lock	Function	Backset	Cylinder	Thumbturn	Indicator	Finish	Handing
XGS	201	-PD95	50	A		-GS07		-32D	-LH
1	2	3	4	5	6	7	8	9	10

ROSE



LEVER



LOCK

-PD95

FUNCTION

- 40 Privacy
- 50 Office / Entry
- 60 Patio
- 70 Classroom
- 95 Security Communicating

5 BACKSET

Backset Blank = 2-3/4"
Backset A = 2-1/2"

6 CYLINDER AND HOUSING (includes collar)

LC = Less Cylinder



Blank = Standard Mortise 1-1/4" Cylinder




- S6 = Small Format Interchangeable Cylinder (SFIC) Housing 1-1/4", 6-Pin, Less Core, L Clover Cam
- S7 = Small Format Interchangeable Cylinder (SFIC) Housing 1-3/8", 7-Pin, Less Core, L Clover Cam
- L6 = Large Format Interchangeable Cylinder (LFIC) Housing 1-1/2", 6-Pin, Less Core, L Clover Cam



Order IC Cores and Thick Door Kits (TDKs) separately

7 THUMBTURN




8 INDICATOR

Blank = Without Indicator
-W = With Indicator

Only GT and GS rosettes are compatible with privacy thumbturn indicator

9 FINISH

Standard:



PVD4 is available for 205, 221, 243, 244, 276, 318, 319, 320, 321, 346 and 509 lever designs.

10 HANDING

-RH = Right Hand -LH = Left Hand