

Commercial Roller Latches

RL300 / RL320


RL300 Dimensions:

Body: 1" Wide x 3-3/8" Long x 1-5/8" Deep
 Strike: 1-11/16" Wide x 2-3/16" Long x 5/32" Thick

RL320 Dimensions:

Body: 1-1/8" Wide x 2-1/4" Long x 1-3/4" Deep
 Strike: 1-1/8" Wide x 2-3/4" Long x 1/16" Thick

RL300 Features

- Actuation is simple, closing of the door causes the roller to fall in the depression of the strike, thereby holding the door closed
- The projection of the roller is easily adjusted using adjusting screws on the face of the unit
- Maximum projection of the roller is 3/8" allowing for variance in the door clearance
- Nylon Roller Standard
- Forged Brass Construction
- Meets ANSI/BHMAA156.16, E19091

RL320 Features

- Actuation is simple, closing of the door causes the roller to fall in the depression of the strike, thereby holding the door closed
- The projection of the roller is easily adjusted by turning knurled knob on back of latch
- Maximum projection of the roller is 1/2" allowing for variance in the door clearance
- Fits heavy-duty cylindrical lock cutout
- Nylon Roller Standard
- Brass or Stainless Steel Construction
- Meets ANSI/BHMAA156.16, E19101

Warranty

3 Year Warranty

Specification

Roller Latch shall be by INOX® Model number RL300 or RL320. All roller latches shall have forged brass construction with Nylon Roller. The projection of the roller shall be easily adjusted.

Finishes

Stocking: US26D (626) Satin Chrome
 Special Order:

- US3 (605) Bright Brass
- US4 (606) Satin Brass
- US10B (613) Oil Rubbed Bronze
- US26 (625) Bright Chrome
- US15 (619) Satin Nickel

Code Compliance


- ANSI A156.16 E19091
- C-UBC-California Amended Uniform Builders Code
- NFPA 80 - National Fire Protection Association - 1999
- NFPA 101 - National Fire Protection - Life Safety